

DG-PS1010U

Supports Multiple Network Protocols

The DG-PS1010U supports one USB 2.0 interface for seamless connection to most printers available in the market today. The DG-PS1010U also supports major network protocols like TCP/IP, IPX/SPX, NetBEUI, AppleTalk, LPR, RAW TCP/IP, SMB over TCP/IP. With its compact design, DG-PS1010U can easily be accommodated anywhere!

Ease of installation

The DG-PS1010U is easily managed using a windows-based configuration utility. Utility can automatically discover the print servers in the LAN and run a wizard for configuring a print server. DG-PS1010U also supports web based administration. Using a Web browser on a PC in LAN simplifies the configuration of the print server. DG-PS1010U also supports tel net for configuration purpose.

Simplified Network printing

DIGISOL DG-PS1010U supports USB interface which offers seamless connection to most printers present in market. DIGISOL DG-PS1010U provides best solution for network based printing to small and home offices, educational institutions, and businesses that need sharing of printers across a network.

USB 2.0 1 Port Print Server integrates LAN using Ethernet or Fast Ethernet network



DG-PS1010U

DIGISOL DG-PS1010U is a compact USB print server that integrates with your LAN using Ethernet or Fast Ethernet network.

It allows wired or wireless stations in your LAN to access and share a USB printer, no matter where they reside in the LAN.

Product Features & Compliances

- USB Print Server - DG-PS1010U
- USB2.0 Compliant
- Supports Email Alert
- Easy to use setup wizard
- SNMP & HP Web JetAdmin
- Supports DHCP (client)
- Supports Internet Printing Protocol (IPP)
- Supports Windows Print Monitor Technology
- Supports 10/100Mbps Auto-sensing UTP port

Technical Specifications

Hardware Specification

- Flash 1Mbytes
- System Memory 8Mbytes
- USB Interface USB2.0 (high speed) standard compliant host controller
- LAN Port 10/100Mbps, auto-sensing
- Reset Button Yes (Reset/Load Factory Defaults)

Network Protocol Support

- TCP/IP
- IPX/SPX
- NetBEUI
- AppleTalk
- LPR
- RAW TCP/IP
- SMB over TCP/IP

Supported Network Operating System

- Windows 95/98/98SE/Me
- Windows NT 4.0/2000/XP/Vista/Win7
- Mac OS 8.1 or higher
- UNIX/Linux
- NetWare (Bindery/NDS)

Management

- Web interface
- Windows-based Setup Program (Utility)
- SNMP
- HP Web JetAdmin

Software Upgrade

- Web interface
- Windows-based Setup Program (Utility)
- TFTP

Power Supply

- 5V/2A, switching

Dimensions

- 73.5(Length) x 63(Width) x 30(Height) mm

EMI Certifications

- CE, FCC Class B

Environmental Specifications

- Operating temperature: 0°C-50°C
- Storage temperature: 5°C-65°C
- Humidity: Operating: 0%-70 %
- Storage: 0%-80 %



Power Connectors
Connects to power adapter

LAN Connect &
Network devices



Ordering Information:

DG-PS1010U: DIGISOL USB 2.0 1 Port Print Server

**Please refer warranty document on www.digisol.com

DIGISOL, the DIGISOL Logo are trademarks and/or registered trademarks of Smartlink Network Systems Ltd. Other trademarks, product, service and company names mentioned are the property of their respective owners. Information is subject to change without notice. The actual product appearance may differ from the one shown here. © 2012 Smartlink Network Systems Ltd. All rights reserved.